


Product Characteristics Thermo-Lite Board®

ISO 9001:2000 Registered




"When you value the importance of your quality products, consider SpaceAge Synthetics, Inc."

SpaceAge Synthetics' Thermo-Lite Board® is manufactured by our skilled employees with high tech equipment in an environmentally friendly and OSHA compliant facility.

All of our products are manufactured under a Quality Management System that is proudly registered to ISO 9001:2000, ensuring every tough sheet is produced for lifetime performance.

We use the finest polyurethane and fiberglass available, and are pleased to offer a full manufacture's warranty; guaranteeing our quality products will remain non absorbent, stable, tough, and free from defects in material or workmanship under normal and nonabusive use. It is the responsibility of the customer to ultimately qualify the product for its intended specific application.



Sheets are run through our sander where the surface is sanded on one or both sides.



Elephant: Tough-looking texture imprinted on the material surface in process.



Natural: Innate surface of our manufacturing process without texture.

Negligible water absorption

Resistant to contamination

Will not corrode or deteriorate

Excellent structural stability

Excellent buoyancy

Sanded product on one or both sides will have a thickness tolerance of no more than +/- 0.020". Without sanding, product will have a tolerance of +/- 0.040"

> Fiber-reinforced polyurethane material is subject to minor inconsistent surface variables that are inherent to our process and the polymerization of polyurethane foam. These variables in no way affect the structural integrity of the product. Made primarily for coring applications, the material color will fade over time when exposed to direct sunlight.

The unique characteristics of our Thermo-Lite Board® offer many significant advantages over traditional materials in nearly every area of comparison.

- ◆Lightweight
- ◆Tough
- Resistant to insects
- High specific strength
 Will not change shape or size
- *Closed cell structure
- •Will not harbor mold or fungus
- Superior adhesive substrate
- Accepts standard tooling and hardware
- ABS Certified for use in the marine industry
- Self-extinguishing (when heat source is removed)
- *Will not crack or split under normal stress conditions
- *Easy to cut, glass-over, resin coat, sand, finish, glue, bond, laminate and hot press shape

*Extremely durable

Guaranteed not to rot

We invite you to contact us right away. Let's get started qualifying Thermo-Lite Board® for your application.

Please Contact Us:



SpaceAge Synthetics, Inc. 402 39th Street NW argo, ND 58102 USA Tel: 701.277.5631 Fax: 701.277.5689 wwww.spaceagesynthtics.com